

Dura-Belt, Inc.

Flat Belt Data Sheet

(All are single ply)

4/11/20

Material	Thickness		Shore A Durometer	Anti- static	Weight		Color	Surface Side1/Side2	Temp. (F) Min/Max	Max. Width	UV resistant	Food Grade	Min. Pulley Diameter	Slider Bed
	Inch	mm			lbs./in.-ft	kg/m ²								
TPU	.032"	0.8	83A*	no	0.017	0.99	Clear	matte/shinny	0/130	36"	no	yes**	0.28	no
TPU	.032"	0.8	92A	no	0.017	1.00	Clear	matte/shinny	0/130	36"	no	yes**	0.28	no
TPU	.050"	1.3	83A*	no	0.026	1.55	Black	matte/matte	0/130	34.5"	no	yes**	0.35	no
TPU	.050"	1.3	83A*	yes	0.026	1.55	Black	matte/matte	0/130	34.5"	no	no	0.35	no
TPU	.062"	1.6	83A*	no	0.032	1.92	Clear	matte/shinny	0/130	34.5"	no	yes**	0.38	no
TPU	.062"	1.6	83A*	no	0.032	1.92	Black	matte/matte	0/130	34.5"	no	yes**	0.38	no
TPU	.094"	2.4	83A*	no	0.049	2.91	Orange	matte/matte	0/130	18"	no	yes**	0.50	no
TPU	.125"	3.2	83A*	no	0.065	3.88	Black	matte/matte	0/130	18"	no	yes**	0.75	no
TPU	.125"	3.2	83A*	no	0.065	3.88	Orange	matte/matte	0/130	18"	no	yes**	0.75	no
PVC	.040"	1.0	80A	no	0.021	1.24	Water blue	matte/matte	0/130	18"	no	no	no	no

*Can be softened to 78A durometer.

** Material is food grade, but bacteria might hide in matte surface.